NSN 5305-00-113-6663

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-113-6663 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.526 inches and 0.641 inches **Fastener Length:** Between 0.609 inches and 0.641 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Or Standard:**

6 type

Departure From Cited Designator:

As modified by type of threads

NSN 5305-00-113-6663

Socket Head Cap Screw - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0