NSN 5305-00-113-8480

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-113-8480 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.437 inches and 0.495 inches **Fastener Length:** Between 1.234 inches and 1.266 inches **Head Style:** Fillister **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** Between 0.155 inches and 0.170 inches **First Diameter From Head:** Between 0.243 inches and 0.249 inches **Second Diameter From Head:** Between 0.200 inches and 0.210 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.109 inches and 0.141 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.765 inches and 0.797 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** First diameter thd Material: Steel comp 1010 **Material Specification:** Astm a108 assn standard single material response **Surface Treatment:** Cadmium

Thread Series Designator: Unf

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

NSN 5305-00-113-8480

Externally Relieved Body Screw - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0