NSN 5305-00-113-9358

Machine Screw - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5305-00-113-9358

Thread Direction:
Right-hand
Thread Length:
Between 0.360 inches and 0.452 inches
Fastener Length:
Between 0.531 inches and 0.593 inches
Head Style:
Round extended washer
Head Diameter:
Between 0.427 inches and 0.447 inches
Head Height:
Between 0.096 inches and 0.106 inches
Extended Washer Diameter:
Between 0.490 inches and 0.510 inches
Extended Washer Thickness:
Between 0.028 inches and 0.033 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
28 Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 125000 pounds per square inch
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment: Cadmium and chromate
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416 federal specification single treatment response
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416 federal specification single treatment response Thread Series Designator:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416 federal specification single treatment response Thread Series Designator: Unf
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416 federal specification single treatment response Thread Series Designator: Unf Shelf Life:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8630 Screw Material Specification: Mil-s-6050 military specification single material response Screw Surface Treatment: Cadmium and chromate Screw Surface Treatment Specification: Qq-p-416 federal specification single treatment response Thread Series Designator: Unf Shelf Life: N/a

NSN 5305-00-113-9358

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.