## NSN 5305-00-114-1913

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-114-1913 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 2.760 inches and 4.000 inches **Fastener Length:** Between 2.960 inches and 4.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.740 inches and 0.750 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: Between 0.625 inches and 0.631 inches Thready Qty Per Inch (tpi): 10 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unc **Specification Or Standard:** 

6 type

**Departure From Cited Designator:** 

As modified by locking feature

## NSN 5305-00-114-1913

Socket Head Cap Screw - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0