NSN 5305-00-114-1914

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-114-1914 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.484 inches and 1.781 inches **Fastener Length:** Between 1.734 inches and 1.781 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.479 inches and 1.500 inches **Head Height:** Between 0.988 inches and 1.000 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 1.000 inches Width Across Flats: Between 0.750 inches and 0.757 inches Thready Qty Per Inch (tpi): 8 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, v type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc **Specification Or Standard:**

6 type

Departure From Cited Designator:

As modified by locking feature

NSN 5305-00-114-1914

Socket Head Cap Screw - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0