# NSN 5305-00-114-1956

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-114-1956



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.282 inches and 0.385 inches

#### Fastener Length:

Between 0.365 inches and 0.385 inches

#### **Head Style:**

Double hexagon w/ hole

#### **Head Height:**

0.260 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

#### **Extended Washer Diameter:**

0.375 inches

#### **Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

#### Hole Diameter:

0.040 inches

### **Thread Diameter:**

0.190 inches

### Hole Quantity:

2

# Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

130000 pounds per square inch

# Hardness Rating:

Between 248.0 brinell hultgren and 341.0 brinell hultgren

# Screw Material:

Iron alloy 660

# Screw Material Specification:

Ams 5732 assn standard single material response

# Head Hole Configuration Style:

Double hexagon longitudinal hole

# Bearing Surface Of Head Surface Finish:

63.0 microinches

# **Thread Series Designator:**

Unc

## Shelf Life:

N/a

# NSN 5305-00-114-1956

Machine Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A500d0

