NSN 5305-00-114-1967

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-114-1967 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.271 inches and 0.326 inches **Fastener Length:** Between 0.488 inches and 0.535 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.496 inches and 0.510 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches grip **Special Features:** Aluminum grommet 0.012 in. Thk on bearing surface of head Steel comp 430fse or steel comp 81b45 or steel comp 4140 or steel comp 302b **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-114-1967

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0