## NSN 5305-00-115-1377

Cadmium and chromate

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-115-1377

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.250 inches
Fastener Length:
Between 0.343 inches and 0.375 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Washer Quantity:
2
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Secondary Washer Relationship To Primary Washer:
Not identical
Secondary Washer Style:
Flat
Primary Washer Outside Diameter:
0.250 inches
Secondary Washer Outside Diameter:
Between 0.253 inches and 0.263 inches
Primary Washer Style:
Split helical ring
Primary Washer Material Thickness:
0.031 inches
Secondary Washer Material Thickness:
Between 0.013 inches and 0.019 inches
Material:
Steel comp 1010 or steel or steel comp 1025
Material Specification:
Qq-s-634 federal specification 1st material response or qq-s-698 1/2 hard federal specification 2nd material response or mil-s-7952 military
specification 3rd material response
Surface Treatment:

## NSN 5305-00-115-1377

Assembled Washer Screw - Page 2 of 2



Surface	<b>Treatment</b>	Specification:
---------	------------------	----------------

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7952 spec.