NSN 5305-00-115-3285

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-115-3285 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.210 inches and 0.230 inches **Fastener Length:** Between 0.455 inches and 0.485 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches **First Diameter From Head:** Between 0.117 inches and 0.123 inches **Second Diameter From Head:** Between 0.095 inches and 0.098 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.225 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.245 inches and 0.255 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** +4a-wl1a, fscm 97424 mfr ref single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-00-115-3285

Externally Relieved Body Screw - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A003b0