

View Online at <https://aerobasegroup.com/nsn/5305-00-115-3285>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.210 inches and 0.230 inches

**Fastener Length:**

Between 0.455 inches and 0.485 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.072 inches and 0.082 inches

**First Diameter From Head:**

Between 0.117 inches and 0.123 inches

**Second Diameter From Head:**

Between 0.095 inches and 0.098 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.225 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.245 inches and 0.255 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

+4a-wl1a, fscm 97424 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0