NSN 5305-00-115-5893

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-115-5893

Thread Class.
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.990 inches and 1.010 inches
Fastener Length:
2.250 inches
Head Style:
Knurled no. 1
Head Diameter:
Between 0.740 inches and 0.760 inches
Head Height:
Between 0.553 inches and 0.573 inches
Shoulder Diameter:
0.490 inches and 0.510 inches first shoulder
Shoulder Length:
0.057 inches and 0.077 inches first shoulder
Hole Diameter:
0.072 inches
Point Style:
Flat
Thread Diameter:
0.190 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Hole Configuration Style:
Hexagon longitudinal hole
Shoulder Shape:
Round first shoulder
Product Name:
Navy special project
Special Features:
0.045 in.Min 0.050 in maximum diameter hole on shank near tip
Material:
Steel comp 4130
Material Specification:

Mil-s-6758 military specification single material response

NSN 5305-00-115-5893

Thumbscrew - Page 2 of 2

Mil-std (military Standard):

Mil-s-6758 spec.



Surface Treatment:
Cadmium
Surface Treatment Specification:
10023, fscm 26512 mfr ref single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0