NSN 5305-00-115-6250

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-115-6250 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.735 inches and 0.795 inches **Fastener Length:** Between 3.110 inches and 3.140 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.160 inches and 0.178 inches Width Between Flats: Between 0.245 inches and 0.250 inches **Extended Washer Diameter:** Between 0.390 inches and 0.410 inches **Extended Washer Thickness:** Between 0.015 inches and 0.202 inches **First Diameter From Head:** Between 0.166 inches and 0.172 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 2.345 inches and 2.375 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 90000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 1020 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Chromate **Surface Treatment Specification:** 135410027 fscm 94990 mfr ref single treatment response

Unf

Thread Series Designator:

NSN 5305-00-115-6250

Externally Relieved Body Screw - Page 2 of 2



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0