## NSN 5305-00-115-9965

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-115-9965
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.084 inches and 0.141 inches
Fastener Length:
Between 0.109 inches and 0.141 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.091 inches and 0.096 inches
Head Height:
Between 0.057 inches and 0.060 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.060 inches
Width Across Flats:
Between 0.050 inches and 0.051 inches
Thready Qty Per Inch (tpi):
80
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel
Material Specification:
66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66
federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material
response
Surface Treatment:
Oxide
Surface Treatment Specification:
-1I-c-13924 cl 4 military specification single treatment response
Thread Series Designator:
Unf
Specification Or Standard:
6 type
Shelf Life:

N/a

## NSN 5305-00-115-9965

Socket Head Cap Screw - Page 2 of 2



Unit Of N	leasure:
-----------	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.