
NSN 5305-00-115-9995

Socket Head Cap Screw - Page 1 of 2





Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.978 inches and 1.207 inches
Fastener Length:
Between 1.484 inches and 1.531 inches
Head Style:
Flat countersunk
Head Diameter:
Between 1.112 inches and 1.188 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
0.375 inches
Thready Qty Per Inch (tpi):
11
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Countersink Angle:
Between 80.0 degrees and 84.0 degrees
Material:
Steel
Material Specification:
Fed standard 66 aisi/ase 302 or 304 or 305 or 384 or astm-a493composition xm-7 federal standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Specification Or Standard:
4 type
Shelf Life:
N/a

NSN 5305-00-115-9995

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

