NSN 5305-00-119-7406

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-119-7406

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.444 inches and 0.511 inches
Fastener Length:
Between 0.704 inches and 0.751 inches
Head Style:
Pan
Head Diameter:
Between 0.594 inches and 0.615 inches
Head Height:
Between 0.203 inches and 0.218 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
63.0 microinches grip
Product Name:
Navy special project
Material:
Titanium alloy uns r54520
Material Specification:
Nas 621 comp 6al-4v assn standard 1st material response or ams 4928 assn standard 2nd material response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

NSN 5305-00-119-7406

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0