NSN 5305-00-119-7413

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-119-7413



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.400 inches and 0.467 inches Fastener Length: Between 0.722 inches and 0.769 inches **Head Style:** Pan **Head Diameter:** Between 0.437 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 63.0 microinches grip **Product Name:** Navy special project Material: Titanium alloy uns r54520 **Material Specification:** Nas 621 comp 6al-4v assn standard 1st material response or ams 4928 assn standard 2nd material response **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5305-00-119-7413

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

