## NSN 5305-00-119-7414

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-119-7414 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.400 inches and 0.467 inches **Fastener Length:** Between 0.598 inches and 0.645 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 63.0 microinches grip **Product Name:** Navy special project Material: Titanium alloy uns r54520 **Material Specification:** Nas 621 comp 6al-4v assn standard 1st material response or ams 4928 assn standard 2nd material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-119-7414

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0