NSN 5305-00-119-7414

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-119-7414

| Thread Class | c. |
|----------------|---|
| 3а | |
| Thread Direct | tion: |
| Right-hand | |
| Thread Lengt | h: |
| Between 0.40 | 0 inches and 0.467 inches |
| Fastener Len | gth: |
| Between 0.598 | 8 inches and 0.645 inches |
| Head Style: | |
| Pan | |
| Head Diamete | er: |
| Between 0.47 | 3 inches and 0.492 inches |
| Head Height: | |
| Between 0.16 | 2 inches and 0.175 inches |
| Grip Diamete | r: |
| Between 0.24 | 85 inches and 0.2495 inches |
| Internal Drive | Style: |
| High-torque | |
| Thread Diame | eter: |
| 0.250 inches | |
| Grip Length: | |
| Between 0.17 | 8 inches and 0.198 inches |
| Thready Qty | Per Inch (tpi): |
| 28 | |
| Min. Tensile S | Strength (psi): |
| 160000 pound | ds per square inch |
| Surface Finis | h: |
| 63.0 microinch | nes grip |
| Product Nam | e: |
| Navy special p | project |
| Material: | |
| Titanium alloy | uns r54520 |
| Material Spec | ;ification: |
| Nas 621 comp | 6 6al-4v assn standard 1st material response or ams 4928 assn standard 2nd material respons |
| Thread Series | s Designator: |
| Unf | |
| Shelf Life: | |
| N/a | |
| Unit Of Meas | ure: |
| | |
| Demilitarizati | on: |
| No | |

NSN 5305-00-119-7414

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

