## NSN 5305-00-119-7635

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-119-7635

Thread Class:
3a Through Directions
Thread Direction:
Right-hand Thread Longth
Thread Length:
Between 0.100 inches and 0.168 inches
Fastener Length:
Between 0.172 inches and 0.204 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.126 inches and 0.176 inches
Locking Feature:
Patch threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1741 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-00-119-7635

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0