

View Online at <https://aerobasegroup.com/nsn/5305-00-121-2287>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.750 inches and 2.000 inches

Fastener Length:

Between 4.150 inches and 4.250 inches

Head Height:

Between 0.455 inches and 0.483 inches

Width Between Flats:

Between 1.100 inches and 1.125 inches

Shank Unthreaded Hole Diameter:

0.138 inches first hole and 0.146 inches first hole

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

120000 pounds per square inch

Hardness Rating:

23.0 rockwell c and 32.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.021 inches first hole and 4.041 inches first hole

Material:

Steel

Material Specification:

Sae gr 5 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

2 type and 10 style and 5 grade

Departure From Cited Designator:

As modified by cotter pin hole and class of thd

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0