

View Online at <https://aerobasegroup.com/nsn/5305-00-121-7745>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.313 inches and 0.363 inches

**Fastener Length:**

Between 1.073 inches and 1.103 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.306 inches and 0.313 inches

**Head Height:**

Between 0.103 inches and 0.118 inches

**Hole Diameter:**

0.046 inches

**Locking Feature:**

Pellet threads or strip threads or patch threads

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Round

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, cond d4 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.