NSN 5305-00-121-8118

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-121-8118 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.619 inches and 0.650 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.130 inches and 0.144 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Hardness Rating:** 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.494 inches and 0.506 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.025 inches Material: Steel comp 1050 primary washer **Material Specification:** Sae assn standard single material response primary washer **Surface Treatment:** Cadmium **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-121-8118

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0