## NSN 5305-00-121-8895

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-121-8895 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.282 inches and 0.333 inches **Fastener Length:** Between 1.543 inches and 1.563 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Locking Feature:** Detent ball grip **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.125 inches and 1.141 inches Thready Qty Per Inch (tpi): 28 **Hardness Rating:** 36.0 rockwell c and 41.0 rockwell c **Countersink Angle:** 100.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.443 inches first hole and 1.563 inches first hole **Surface Finish:** 63.0 microinches top of head Material: Steel **Material Specification:** 

Steel

Material Specification:

Mil-b-83050 military specification single material response

Surface Treatment:

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416 type 2 cl 2 federal specification single treatment response

## NSN 5305-00-121-8895

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-b-83050 spec.