NSN 5305-00-122-0027

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-122-0027 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.219 inches and 0.281 inches **Fastener Length:** Between 0.281 inches and 0.343 inches **Head Style:** Fillister **Head Diameter:** Between 0.344 inches and 0.406 inches **Head Height:** Between 0.147 inches and 0.167 inches **Hole Diameter:** 0.062 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch **Screw Material:** Steel comp 8630 or steel **Screw Material Specification:** Qq-s-684, comp 4130_canc federal specification 2nd material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, class 3 federal specification single treatment response or f-71, fscm 18355 mfr ref single treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:** Unf Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-00-122-0027

Machine Screw - Page 2 of 2



_		 • •				
n	em	it o	riz	2 †1	n	٠.

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.