## NSN 5305-00-122-3471

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-122-3471 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.312 inches and 0.344 inches **Fastener Length:** Between 1.062 inches and 1.092 inches **Head Style: Button Head Diameter:** Between 0.484 inches and 0.516 inches **Head Height:** Between 0.109 inches and 0.141 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response or qq-s-69 (canceled) federal specification 5th material response **Screw Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Fiig: A500d0 Mil-std (military Standard): Mil-s-5000 spec.

No