NSN 5305-00-122-7141

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-122-7141 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.245 inches and 0.255 inches **Fastener Length:** 0.688 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.307 inches and 0.317 inches **Head Height:** Between 0.296 inches and 0.328 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.334 inches and 0.354 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point style 6, 0.095 in. Dia, 0.094 in. Lg by 90 degrees angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-122-7141

Externally Relieved Body Screw - Page 2 of 2



_			٠.								
n	Δ	m	ш	11	o r	17	9	H	^	n	
_	ㄷ		•	IL	aı.	14	а	LI	u		

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.