NSN 5305-00-122-7713

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-122-7713 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.714 inches and 0.829 inches **Fastener Length:** Between 0.797 inches and 0.829 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Hole Diameter:** 0.047 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Round internal hexagon Material: Steel comp 410 **Material Specification:** Ams 5613 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjc Shelf Life:

N/a

NSN 5305-00-122-7713

Socket Head Cap Screw - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A003b0