

View Online at <https://aerobasegroup.com/nsn/5305-00-123-2574>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.234 inches and 0.266 inches

**Fastener Length:**

Between 0.796 inches and 0.828 inches

**Head Style:**

Knurled no. 4

**Head Diameter:**

Between 0.296 inches and 0.328 inches

**Head Height:**

Between 0.296 inches and 0.328 inches

**First Diameter From Head:**

Between 0.115 inches and 0.125 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.436 inches and 0.500 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Cone point no.6, 0.094 in. Lg, 0.120 in.Dia, 90 degree angle

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-14072, finish no. E300 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-14072 spec.