NSN 5305-00-123-2574

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-123-2574 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.234 inches and 0.266 inches **Fastener Length:** Between 0.796 inches and 0.828 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.296 inches and 0.328 inches **Head Height:** Between 0.296 inches and 0.328 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.436 inches and 0.500 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point no.6, 0.094 in. Lg, 0.120 in.Dia, 90 degree angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-14072, finish no. E300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-123-2574

Externally Relieved Body Screw - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-14072 spec.