NSN 5305-00-124-2599

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-124-2599 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.120 inches and 0.188 inches **Fastener Length:** Between 0.156 inches and 0.188 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.136 inches and 0.140 inches **Head Height:** Between 0.083 inches and 0.086 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.062 inches and 0.064 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 70000 pounds per square inch **Hardness Rating:** 80.0 rockwell b and 85.0 rockwell b Material: Steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-t-704 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No Fiig:

A003b0

NSN 5305-00-124-2599

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-t-704 spec.