
Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-125-5704

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.141 inches and 0.204 inches Fastener Length: Between 0.172 inches and 0.204 inches Head Style: Flat chamfer Head Style: Flat chamfer Head Norther: Between 0.112 inches and 0.118 inches Head Style: Pread Dimeter: Between 0.070 inches and 0.073 inches Head Style: Vieth Across Flats: Between 0.062 inches and 0.063 inches Thread Diameter: 0.073 inches With Across Flats: Between 0.062 inches and 0.063 inches Thready Oty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80.000 pounds per square inch Hardness Rating: 80.000 pounds per square inch Minimum Yield Strength: 9000 pounds per square inch Materia! Stel comp 302 or stel comp 303 or stel comp 304 or stel comp 305 or stel comp 316 Materia! Stel comp 302 or stel comp 303 or stel comp 304 or stel co	view Online at https://aerobasegroup.com/nsn/5305-00-125-5704
Tread Direction: Right-hand Thread Length: Between 0.141 inches and 0.204 inches Fastener Length: Between 0.172 inches and 0.204 inches Head Style: Flat chamfer Head Diameter: Between 0.112 inches and 0.118 inches Head Height: Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches Mitht Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 8000 pounds per square inch Hardness Rating: 8000 pounds per square inch Minimum Yield Strength: 30000 pounds per square inch Material: Stel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material: 64 federal standard all material responses Striftcattomet: Passivate	Thread Class:
Right-hand Thread Length: Between 0.141 inches and 0.204 inches Fastener Length: Between 0.172 inches and 0.204 inches Head Style: Flat chamfer Head Diameter: Between 0.112 inches and 0.118 inches Head Height: Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80.0000 pounds per square inch Hardness Rating: 80.000 pounds per square inch Minimur Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 316 Material:	За
Thread Length: Between 0.141 inches and 0.204 inches Fastener Length: Between 0.172 inches and 0.204 inches Head Style: Flat chamfer Head Diameter: Between 0.112 inches and 0.118 inches Head Height: Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thread Qt Per Inch (tpi): 64 Min. Tensile Strength (psi): 8000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimur Yield Strength: 3000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material: 64 fedral standard all material responses Burtical Strength: 8000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp	Thread Direction:
Astener Length: Between 0.172 inches and 0.204 inches Head Style: Flat chamfer Head Diameter: Between 0.112 inches and 0.118 inches Head Height: Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches With Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80000 pounds per square inch Minimum Yield Strength: 90000 pounds per square inch Material: 90000 pounds per square inch Material: <	Right-hand
Fastener Length: Between 0.172 inches and 0.204 inches Head Style: Flat chamfer Head Diameter: Between 0.112 inches and 0.118 inches Head Diameter: Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.000 pounds per square inch Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 64 federal standard all material responses Surface Treatment:	Thread Length:
Between 0.172 inches and 0.204 inches Head Style: Flat chamfer Head Diameter: Between 0.112 inches and 0.118 inches Head Height: Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 9000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material: 64 federal standard all material responses Strace Treatmet: Passivate	Between 0.141 inches and 0.204 inches
Head Style:Flat chamferHead Diameter:Between 0.112 inches and 0.118 inchesHead Height:Between 0.070 inches and 0.073 inchesInternal Drive Style:HexagonThread Diameter:0.073 inches0.073 inchesWidth Across Flats:Between 0.062 inches and 0.063 inchesThready Qty Per Inch (tpi):64Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.01 ockwell bMinimum Yleld Strength:30000 pounds per square inchHaterial:Stel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316Metrial:64 federal standard all material responsesStrace Treatment:Passivate	Fastener Length:
Flat chamfer Head Diameter: Between 0.112 inches and 0.118 inches Head Height: Between 0.070 inches and 0.073 inches Internal Drive Style: Heagon Thread Diameter: 0.073 inches With Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minium Yield Strength: 90000 pounds per square inch Material: 90000 pounds per square inch Hardness Rating: 80.0 rockwell b Minium Yield Strength: 90000 pounds per square inch Material: 90000 pounds per square inch	Between 0.172 inches and 0.204 inches
Head Diameter:Between 0.112 inches and 0.118 inchesHead Height:Between 0.070 inches and 0.073 inchesInternal Drive Style:HeagonThread Diameter:0.073 inchesWidth Across Flats:Between 0.062 inches and 0.063 inchesThready Qty Per Inch (tpi):64Min. Tensile Strength (psi):80000 pounds per square inchMinum Yield Strength:90000 pounds per square inchMinum Yield Strength:90000 pounds per square inchMaterial:90000 pounds per square inch90000 pounds per square inch	Head Style:
Between 0.112 inches and 0.118 inches Head Height: Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.00 rockwell b Minimum Yield Strength: 30000 pounds per square inch Hardness Rating: 80.00 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: 6 federal standard all material responses Surface Treatment: Passivate	Flat chamfer
Head Height: Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 64 federal standard all material responses Surface Treatment: Passivate	Head Diameter:
Between 0.070 inches and 0.073 inches Internal Drive Style: Hexagon Thread Diameter: 0.073 inches Width Across Flats: 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 64 Geteral standard all material responses Surface Treatment: Passivate	Between 0.112 inches and 0.118 inches
Internal Drive Style: Hexagon Thread Diameter: 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 64 federal standard all material responses Surface Treatment: Passivate	Head Height:
HexagonThread Diameter:0.073 inchesWidth Across Flats:Between 0.062 inches and 0.063 inchesThready Qty Per Inch (tpi):64Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchBdterial:Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316Material:64 federal standard all material responsesSurface Treatment:Passivate	Between 0.070 inches and 0.073 inches
Thread Diameter: 0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	Internal Drive Style:
0.073 inches Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 8000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 3000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	Hexagon
Width Across Flats: Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	Thread Diameter:
Between 0.062 inches and 0.063 inches Thready Qty Per Inch (tpi): 64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	0.073 inches
Thready Qty Per Inch (tpi):64Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchMaterial:Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316Material Specification:66 federal standard all material responsesSurface Treatment:Passivate	Width Across Flats:
64 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	Between 0.062 inches and 0.063 inches
 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate 	Thready Qty Per Inch (tpi):
80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	64
Hardness Rating:80.0 rockwell bMinimum Yield Strength:30000 pounds per square inchMaterial:Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316Material Specification:66 federal standard all material responsesSurface Treatment:Passivate	Min. Tensile Strength (psi):
80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	80000 pounds per square inch
Minimum Yield Strength:30000 pounds per square inchMaterial:Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316Material Specification:66 federal standard all material responsesSurface Treatment:Passivate	Hardness Rating:
30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	80.0 rockwell b
Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	Minimum Yield Strength:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	30000 pounds per square inch
Material Specification: 66 federal standard all material responses Surface Treatment: Passivate	Material:
66 federal standard all material responses Surface Treatment: Passivate	Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Surface Treatment: Passivate	Material Specification:
Passivate	66 federal standard all material responses
	Surface Treatment:
	Passivate
Surface Treatment Specification:	Surface Treatment Specification:
Qq-p-35 federal specification single treatment response	Qq-p-35 federal specification single treatment response
	Thread Series Designator:
Thread Series Designator:	Unc
-	Shelf Life:
Unc	N/a
Unc Shelf Life:	Unit Of Measure:
Thread Series Designator:	-
-	Shelf Life:
Unc	N/a
Unc Shelf Life:	Unit Of Measure:
Unc Shelf Life: N/a	

NSN 5305-00-125-5704

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

