NSN 5305-00-125-7732

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-125-7732 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.198 inches and 0.205 inches **Head Height:** Between 0.121 inches and 0.125 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.125 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Surface Finish: 125.0 microinches Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Thread Series Designator:** Unc **Specification Or Standard:** 6 type

N/a

Shelf Life:

NSN 5305-00-125-7732

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0