# NSN 5305-00-126-6148

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-126-6148



# Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 1.786 inches and 1.938 inches

#### Fastener Length:

Between 1.848 inches and 1.938 inches

#### Head Style:

Pan

#### Head Diameter:

Between 0.357 inches and 0.373 inches

#### **Head Height:**

Between 0.122 inches and 0.133 inches

## Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.190 inches

## Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### **Screw Material:**

Steel comp 4037 or steel comp 8630

# Screw Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response

#### Screw Surface Treatment:

Cadmium and chromate

# Screw Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response

#### Thread Series Designator:

Unjf

# **Specification Data:**

80205-nas603 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

# NSN 5305-00-126-6148

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-6050 spec.

