

View Online at <https://aerobasegroup.com/nsn/5305-00-127-5392>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.074 inches and 0.114 inches

**Fastener Length:**

Between 0.307 inches and 0.332 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.240 inches and 0.260 inches

**First Diameter From Head:**

Between 0.120 inches and 0.130 inches

**Second Diameter From Head:**

Between 0.059 inches and 0.079 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.125 inches and 0.135 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.156 inches and 0.166 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Countersink Angle:**

Between 98.0 degrees and 102.0 degrees

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0