## NSN 5305-00-127-5392

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-127-5392 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.074 inches and 0.114 inches **Fastener Length:** Between 0.307 inches and 0.332 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.240 inches and 0.260 inches First Diameter From Head: Between 0.120 inches and 0.130 inches **Second Diameter From Head:** Between 0.059 inches and 0.079 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.156 inches and 0.166 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 98.0 degrees and 102.0 degrees **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-127-5392

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0