

View Online at <https://aerobasegroup.com/nsn/5305-00-127-7515>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.387 inches and 0.500 inches

**Fastener Length:**

Between 0.470 inches and 0.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.303 inches and 0.312 inches

**Head Height:**

Between 0.185 inches and 0.190 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.156 inches and 0.159 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell c

**Minimum Yield Strength:**

30000 pounds per square inch

**Material:**

Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp xm-7 fastener

**Material Specification:**

Astm a493 assn standard all material responses fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0