NSN 5305-00-128-1715 Externally Relieved Body Screw - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5305-00-128-1715 | |
|--|--|
| Thread Class: | |
| 3a | |
| Thread Length: | |
| Between 0.318 inches and 0.368 inches | |
| Fastener Length: | |
| Between 0.490 inches and 0.510 inches | |
| Head Style: | |
| Hexagon | |
| Head Height: | |
| Between 0.080 inches and 0.095 inches | |
| Width Between Flats: | |
| Between 0.305 inches and 0.313 inches | |
| First Diameter From Head: | |
| Between 0.135 inches and 0.140 inches | |
| Second Diameter From Head: | |
| Between 0.215 inches and 0.220 inches | |
| Third Diameter From Head: | |
| Between 0.120 inches and 0.125 inches | |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: | |
| Between 0.040 inches and 0.045 inches | |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: | |
| Between 0.112 inches and 0.122 inches | |
| Distance From Largest Bearing Surface Of Head To End Of Third Diameter: | |
| Between 0.142 inches and 0.172 inches | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |
| | |