

View Online at <https://aerobasegroup.com/nsn/5305-00-128-6403>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.172 inches and 0.266 inches

Fastener Length:

Between 0.234 inches and 0.266 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.109 inches and 0.111 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Special Features:

Flat black perma-resin no. 1

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel

Material Specification:

66 federal standard 1st material response or 66 federal standard 2nd material response or 66 federal standard 3rd material response or 66 federal standard 4th material response or 66 federal standard 5th material response or astm-a493 aisi xm-7 assn standard 6th material response

Surface Treatment:

Paint head

Surface Treatment Specification:

Mil-c-3924 cl 3 military specification 1st treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas1352 professional/industrial association standard

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-3924 spec.