

View Online at <https://aerobasegroup.com/nsn/5305-00-130-7645>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.469 inches and 0.519 inches

**Fastener Length:**

Between 1.667 inches and 1.697 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.645 inches and 0.672 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.178 inches and 1.198 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Countersink Angle:**

Between 59.75 degrees and 60.25 degrees

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Bearing surface of head to be grooved to a 0.472 in. Min., 0.474 in. Max. Dia, 0.115 in. Min. 0.120 in. Max. From top of head

**Material:**

Steel comp h11

**Material Specification:**

Ams6485 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0