NSN 5305-00-131-2899

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-131-2899 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.208 inches and 0.228 inches **Fastener Length:** Between 0.615 inches and 0.645 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.387 inches and 0.437 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-131-2899

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0