## NSN 5305-00-132-2716

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-132-2716 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 1.250 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.484 inches and 0.516 inches **Head Height:** 0.560 inches Point Length: 0.180 inches **Point Diameter:** Between 0.159 inches and 0.175 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Point Chamfer Angle:** 90.0 degrees Material: Steel comp 303 **Material Specification:** Qq-s-764, cond a federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Test Data Document:** 98230-0n080065 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-132-2716

Thumbscrew - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.