NSN 5305-00-132-4225

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-132-4225 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.135 inches **Fastener Length:** 0.410 inches **Head Style:** Flat chamfer **Head Diameter:** 0.250 inches **Head Height:** 0.120 inches **First Diameter From Head:** Between 0.124 inches and 0.126 inches **Second Diameter From Head:** Between 0.095 inches and 0.097 inches Third Diameter From Head: Between 0.124 inches and 0.126 inches **Fourth Diameter From Head:** Between 0.085 inches and 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.098 inches and 0.108 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.116 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.143 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.263 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4

•

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

NSN 5305-00-132-4225

A003b0

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 2 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: