NSN 5305-00-132-6868

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-132-6868 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.137 inches and 0.182 inches **Fastener Length:** Between 0.162 inches and 0.182 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.092 inches and 0.096 inches **Head Height:** Between 0.057 inches and 0.060 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.060 inches Width Across Flats: Between 0.048 inches and 0.050 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 70000 pounds per square inch **Hardness Rating:** 80.0 rockwell b and 85.0 rockwell b Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mil-t-704 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-00-132-6868

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-t-704 spec.