## NSN 5305-00-132-6870

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-132-6870

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.117 inches and 1.207 inches
Fastener Length:
Between 1.427 inches and 1.447 inches
Head Style:
Hexagon
Head Height:
Between 0.140 inches and 0.172 inches
Width Between Flats:
Between 0.304 inches and 0.316 inches
Point Length:
Between 0.180 inches and 0.200 inches
Point Style:
Ball
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 33.0 rockwell c
Material:
Steel comp 4130
Material Specification:
Mil-s-6758 military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-00-132-6870

Setscrew - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.