

View Online at <https://aerobasegroup.com/nsn/5305-00-133-7999>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.344 inches

Fastener Length:

0.640 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.247 inches and 0.248 inches

Head Height:

0.329 inches

Shoulder Diameter:

0.295 inches first shoulder and 0.300 inches first shoulder

Shoulder Length:

0.291 inches first shoulder and 0.296 inches first shoulder

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Features Provided:

Casehardened

Thready Qty Per Inch (tpi):

28

Shoulder Shape:

Round first shoulder

Special Features:

Slot on opposite end 0094 in. W

Material:

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1212 or steel comp 1213

Material Specification:

Astm a108 assn standard all material responses

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Dod-p-16232 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.