NSN 5305-00-136-1526

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-136-1526 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.480 inches and 0.520 inches **Fastener Length:** Between 1.480 inches and 1.520 inches **Head Style:** Hexagon **Head Height:** 0.310 inches Width Between Flats: Between 0.740 inches and 0.750 inches **First Diameter From Head:** Between 0.370 inches and 0.390 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.980 inches and 1.020 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 3130 **Material Specification:** Mil-s-16974 military specification single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924, class 2 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-136-1526

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-16974 spec.