NSN 5305-00-137-3071

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-137-3071

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length: Between 0.885 inches and 1.031 inches
Fastener Length: Between 0.985 inches and 1.031 inches
Head Style: Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height: Between 0.492 inches and 0.500 inches
Locking Feature: Strip threads
·
Internal Drive Style:
Hexagon Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Material:
Steel
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Unf
Specification Or Standard:
6 type
- 71-

NSN 5305-00-137-3071

Socket Head Cap Screw - Page 2 of 2



Departure From Cited Designator	Departure	From	Cited	Designator
---------------------------------	-----------	------	-------	------------

As modified by locking feature

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0