NSN 5305-00-137-3137



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-137-3137 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.126 inches **Fastener Length:** 0.188 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.072 inches and 0.082 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 90000 pounds per square inch **Primary Washer Outside Diameter:** Between 0.270 inches and 0.280 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** 0.016 inches Material: Steel comp 403 primary washer or steel comp 405 primary washer or steel comp 410 primary washer or steel comp 414 primary washer or steel comp 416 primary washer or steel comp 416se primary washer or steel comp 420 primary washer or steel comp 430 primary washer or steel comp 431 primary washer or steel comp 440a primary washer or steel comp 440b primary washer or steel comp 440c primary washer or steel comp 446 primary washer or steel comp 430f primary washer **Material Specification:** 66 federal standard all material responses primary washer **Surface Treatment: Passivate Thread Series Designator:** Unc

Unit Of Measure:

Shelf Life:

N/a

NSN 5305-00-137-3137

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0