## NSN 5305-00-138-0183

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-138-0183 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.089 inches and 0.130 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches **First Diameter From Head:** Between 0.070 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.245 inches and 0.255 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 60000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel **Material Specification:** Qq-s-634 federal specification single material response or qq-s-637 federal specification single material response or 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2 cl2 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-138-0183

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0