NSN 5305-00-138-0331

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-138-0331 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.214 inches and 0.255 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches **First Diameter From Head:** Between 0.070 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.120 inches and 0.130 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Material Specification:** Astm a108 assn standard single material response or qq-s-637 federal specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 assn standard 1st treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-138-0331

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0